





PD-5 SERIES

HAND-HELD DISTANCE METER



SPECIFICATIONS

	PD-54N	PD-56N	PD-58N	PD-512N
Measuring Range	0.05m~40m	0.05m~60m	0.05m~80m	0.1m~120m
Measuring Precision(Typical)	±1.5mm	±1.5mm	±1.5mm	±1.5mm
Laser Class	II	II	II	II
Laser Type	620-690 nm, <1mW			
Type	Indoor	Indoor	Outdoor	Outdoor
Operation Temperature	-10°C ~+50°C	-10°C ~+50°C	-10°C ~+50°C	-10°C ~+50°C
Selectable Datum Side	●	●	●	●
Area	●	●	●	●
Pythagoras	●	●	●	●
Volume	●	●	●	●
Plus/minus Calculation	●	●	●	●
Data Storage	○	99	99	99
Time Delay Measurement	○	○	●	●
Metope Measurement	○	○	●	●
Dip angle Measurement	○	○	●	●
Triangle Area	○	○	○	●
Trapezoidal Measurement	○	○	○	●
Distance Stake-Out	○	○	○	●
Graphics Auxiliary Targeting	○	○	○	Cmos Imging Sensor
Display	Three Lines Stroke Segment			2.2" Color Screen
Battery	AAA2x1.5V			Lithium Battery
Battery Life	5000			20000
IP	IP54			IP54
Size	121x45x25(mm)			137x52x29(mm)



PD-54N



PD-56N



PD-58N



PD-512N